



GOLDEN

Elegant lighting for everyday living

PARTS & ASSEMBLY SHEET






Fixture Name: **Torbellino 8106-BP3 CDB**

This fixture assembled PO: _____ Date: _____

Notice: Please review the parts listing and check for all parts before assembling the fixture. If any parts are missing or damaged, please note on this sheet and contact the place of purchase to arrange for replacement parts.

PARTS LIST

Company Name: _____ Co. Account #: _____
to be filled out by retailer

Canopy 1ea $\Phi 153 \times 32$ Hmm 	Mounting Screws 2ea 8/32T*1-1/4"L 	Top loop 1ea $\Phi 62 \times 68$ Hmm 
Chain 1ea 6ft*4.2mm 	Wire connectors 2ea Orange 	Bottom cap 1ea $\Phi 70 \times 11$ Hmm 
Chain connector 2ea 23.8*59mm 	Canopy loop and Canopy loop collar 1ea $\Phi 25 \times 45$ Hmm 	Nipple 2ea $\Phi 12 \times 55$ mm 
Mounting Strap 1ea 100mm*20mm 	Hex Nut 2ea $\Phi 9$ mm*4mm 	Finial 1ea $\Phi 36 \times 55$ Hmm 

Part Needed _____	Quantity _____
Part Needed _____	Quantity _____
Reason why (missing, scratched, broken glass, bent, bad finish)	
Comments _____	

FIXTURE ASSEMBLY INSTRUCTIONS


Read and review installation instruction sheet before assembling the fixture.

1. Thread the Body (L) onto the Coupling (M) and until tight.
2. Feed the fixture wires through the Top loop (J) and pull the wires until taut.
3. Then screw the Top Loop (J) to the threaded Nipple (K) at top of Frame until tight.

NOTE: INSTALL THE GLASS ASSEMBLY AFTER THE FIXTURE IS HUNG.

8106-BP3 CDB

Fig 1



For Customer Service, contact the place of purchase to arrange for replacement parts.

PARTS & ASSEMBLY SHEET

Fixture Name: Torbellino 8106-BP3 CDB

4. By measuring determine correct number of links needed for proper hanging height. Use a pair of pliers to open one link of the Chain (C2) then remove the excess Chain (C2) and discard it.
5. Use one chain connector(E2) to attach one end of the chain to the Top loop (D2) and close the chain connector.
6. Feed the fixture wires through the Chain (every three links) and pull the wires until taut.
7. Slip Canopy loop collar (B2) over the chain, then do the same with the canopy (F2).
8. When ready to complete the installation Use the other chain connector and attach the other end of the chain to the canopy loop (A2) and close the chain connector.
9. Make sure the weight of the chandelier is supported by the chain-not the electrical wire.

You may now install the fixture.

NOTE: Complete these remaining steps after the fixture is hung.

10. Thread the Nipple (S) into the Coupling (R), and then thread the Hex Nut (T) onto Nipple (S) until tight.
11. Install the light bulbs in accordance with the fixture's specifications.
12. Place Glass Shade (N) over the Metal Ring (S). The Nipple (S) shall protrude through the bottom hole of the Glass Shade (U).
13. While holding the Glass Shade slide the Rubber Washer (V) onto the Nipple(S).
14. Slide Bottom Cap (X) over Nipple (S) and thread the Finial (Y) until tight.
15. Attach each half of the Diffuser (N) on the circular plate of the Metal ring (S) using the Deco nuts (P) and rubber washers attached. Place one rubber washer on each side of the Diffuser glass (N) to protect from breakage.
(DO NOT EXCEED THE MAXIMUM WATTAGE RATING)

Fig 2





Fig 3



For Customer Service, contact the place of purchase to arrange for replacement parts.

WARNING! SHUT OFF POWER AT FUSE OR CIRCUIT BREAKER.

HANGING THE FIXTURE (Fig.1)

- Carefully remove the new fixture from the carton and the yellow bag that holds all parts. Check that all parts are included as shown in the illustration and parts list.
- Shut off the power at the circuit breaker and remove old fixture from ceiling, including the old mounting strap.
- Thread Nipple(C) into Canopy Loop (F) until snug.
- Thread other end of the Nipple (C) with Canopy Loop attached into Mounting Strap (D).
- Place Lock Washer (B) over end of Nipple (C) protruding through Mounting Strap (D) and thread Hex Nuts (A) onto Nipple until tight.
- Take this mounting strap assembly and mount to ceiling junction box with junction box Screws (E). Tighten screw securely with screw driver.
- Unscrew the Canopy loop collar (H) from the Canopy loop. Take the canopy and pass over the Canopy loop. approximately one half of the canopy loop exterior threads should be exposed. Adjust until desired height is reached. *the Canopy loop collar should fit snugly on the Canopy loop after the canopy is installed. Remove Canopy and Canopy lock collar.
- Assemble the fixture and have an assistant or secure support hold the weight of the fixture while you complete the wiring connections.
- Thread the fixture wires and ground wire of the assembled fixture through the canopy loop and nipple and into the outlet box.

CONNECTING THE WIRES (Fig 2)

- Attach the power supply wires to the fixture lead wires by connecting BLACK to BLACK (or SMOOTH) and WHITE to WHITE (or RIBBED).
- Attach the GROUND wire(GREEN or COPPER) from the Junction Box and the fixture Ground wire to the green Ground Screw on the Mounting Bracket (D) or connect both wires together using the correct size of wire connectors.
- NOTE: Twist the wires together in the same direction you twist the wire connector onto the wires.
- Tuck these wire connections neatly into the Junction Box.
- Raise Canopy (G) to the ceiling and secure in place by tightening the Canopy loop collar(H) into the Canopy Loop(F)
- Install the light bulbs and glass shade as per the fixture assembly sheet.

Fig. 1





Fig. 2



**YOUR INSTALLATION IS NOW COMPLETE.
RETURN POWER TO THE JUNCTION BOX
AND TEST THE FIXTURE.**